### Thermoplastic Valves **Industrial PVC Backwater Valves**



Backwater Valves are designed to prevent backflow in numerous applications where easy service access for maintenance and cleaning is needed. Excellent for use in sanitary or storm sewer drainage systems to prevent waste back up due to inadequate drainage, for balancing multi-level ponds, aquaculture features or storage tank systems, and many other applications. Spears® Backwater Valve has been engineered for improved function and easier service, especially in buried service with use of optional Service-Access Extension available either preassembled with valve or as an add-on kit.

- Replaceable internal flapper assembly with EPDM Seat.
- Service-Access Extension available either preassembled with valve, as an add-on kit, or as valve & extension kit components with user supplied pipe.

  Direct Connection to ASTM D 2665 PVC DWV or other IPS size pipe. Spears\* fabricated IPS x Sewer Adapters or DWV x Sewer & Drain Adapter Bushings are available for connection to ASTM D 3034 & ASTM D 2729 Sewer pipe.
- Pressure Rated to 43 psi (100 feet of head) @ 73°F (23°C).
  All extension kits can be cut shorter for custom application.
- - Conforms to ASME/ANSI A112.14.1 for Backwater Valves.

### **PVC Backwater Valves**



## **PVC Backwater Valves** Soc x Soc - Valve Only

Part Number	Size	Std	Mstr	Disc	Price
r art indiliber	Size	Pk	Ctn	Code	Each
S275P	2	1	12	055	56.10
S375P	3	2	0	055	56.21
S475P	4	1	0	055	62.27
S675P	6	1	0	055	265.30

## **PVC Backwater Valves with Extension Kit to Premade Length**



# **PVC Backwater Valves with Extension Kit to Premade**

#### Soc x Soc - Assembled with Extension

SUC X SUC - ASSEMBLED WITH EXTENSION								
Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each			
S275P-120 <sup>1</sup>	2X12HT	1	0	055	169.21			
S275P-160 <sup>1</sup>	2X16HT	1	0	055	182.01			
S275P-2001	2X20HT	1	0	055	194.80			
S275P-240 <sup>1</sup>	2X24HT	1	0	055	207.60			
S275P-3601	2X36HT	1	0	055	218.04			
S275P-4801	2X48HT	1	0	055	239.64			
S375P-120 <sup>1</sup>	3X12HT	1	0	055	169.21			
S375P-160 <sup>1</sup>	3X16HT	1	0	055	182.01			
S375P-2001	3X20HT	1	0	055	194.80			
S375P-240 <sup>1</sup>	3X24HT	1	0	055	207.60			
S375P-3601	3X36HT	1	0	055	218.04			
S375P-480 <sup>1</sup>	3X48HT	1	0	055	239.64			
S475P-120 <sup>1</sup>	4X12HT	1	0	055	219.79			

# **PVC Backwater Valves with Extension Kit to Premade**

### Soc x Soc - Assembled with Extension (continued)

COCK COC / COCKINGION WITH EXTENSION (CONTINUES)						
Part Number	Size	Std	Mstr	Disc	Price	
rait Nullibei	Size	Pk	Ctn	Code	Each	
S475P-160 <sup>1</sup>	4X16HT	1	0	055	237.11	
S475P-2001	4X20HT	1	0	055	252.89	
S475P-2401	4X24HT	1	0	055	269.66	
S475P-3601	4X36HT	1	0	055	283.20	
S475P-480 <sup>1</sup>	4X48HT	1	0	055	311.22	
S675P-1201	6X12HT	1	0	055	461.53	
S675P-160 <sup>1</sup>	6X16HT	1	0	055	497.93	
S675P-2001	6X20HT	1	0	055	531.07	
S675P-2401	6X24HT	1	0	055	566.35	
S675P-3601	6X36HT	1	0	055	594.74	
S675P-480 <sup>1</sup>	6X48HT	1	0	055	653.55	
1 Cine decimates no	admed continue almost a sustainal.	and backer	LA /LIT		-1 4- 46	

- Size designates nominal valve size x extension height (HT-top of valve to top of extension, inches)

## **PVC Service-Access Extension Kit Only to Premade** Length



PVC Service-Access Extension Kit: includes factory assembled internal flap assembly, assembly extension pipe, and external extension housing with top access adapter. Requires solvent cement assembly to existing valve and uses existing threaded Access Plug. Standard Extensions are available in convenient increments of 12", 16", 20", 24", 36", and 48" (measured from top of valve to top of extension). Contact Spears® for pricing on custom cut lengths. All extension kits can be cut shorter in the field for custom fits prior to cementing access adapter in place.

# **PVC Service-Access Extension Kit Only to Premade**

Longin					
Part Number	Size	Std	Mstr	Disc	Price
art Number	OIZE	Pk	Ctn	Code	Each
SAEK-020-120 <sup>1</sup>	2X12HT	1	0	055	52.77
SAEK-020-160 <sup>1</sup>	2X16HT	1	0	055	54.28
SAEK-020-200 <sup>1</sup>	2X20HT	1	0	055	55.72
SAEK-020-240 <sup>1</sup>	2X24HT	1	0	055	58.39
SAEK-020-360 <sup>1</sup>	2X36HT	1	0	055	61.15
SAEK-020-480 <sup>1</sup>	2X48HT	1	0	055	64.14
SAEK-030-120 <sup>1</sup>	3X12HT	1	0	055	57.23
SAEK-030-160 <sup>1</sup>	3X16HT	1	0	055	64.60
SAEK-030-2001	3X20HT	1	0	055	68.44
SAEK-030-240 <sup>1</sup>	3X24HT	1	0	055	77.13
SAEK-030-360 <sup>1</sup>	3X36HT	1	0	055	91.24
SAEK-030-480 <sup>1</sup>	3X48HT	1	0	055	107.91
SAEK-040-120 <sup>1</sup>	4X12HT	1	0	055	85.34
SAEK-040-160 <sup>1</sup>	4X16HT	1	0	055	96.21
SAEK-040-200 <sup>1</sup>	4X20HT	1	0	055	118.67
SAEK-040-240 <sup>1</sup>	4X24HT	1	0	055	129.95



### Thermoplastic Valves **Industrial PVC Backwater Valves**

Backwater Valves are designed to prevent backflow in numerous applications where easy service access for maintenance and cleaning is needed. Excellent for use in sanitary or storm sewer drainage systems to prevent waste back up due to inadequate drainage, for balancing multi-level ponds, aquaculture features or storage tank systems, and many other applications. Spears® Backwater Valve has been engineered for improved function and easier service, especially in buried service with use of optional Service-Access Extension available either preassembled with valve or as an add-on kit.

- Replaceable internal flapper assembly with EPDM Seat.
- Service-Access Extension available either preassembled with valve, as an add-on kit, or as valve & extension kit components with user supplied pipe.

  Direct Connection to ASTM D 2665 PVC DWV or other IPS size pipe. Spears® fabricated IPS x Sewer Adapters or DWV x Sewer & Drain Adapter Bushings are available for connection to ASTM D 3034 & ASTM D 2729 Sewer pipe.
- Pressure Rated to 43 psi (100 feet of head) @ 73°F (23°C).
- All extension kits can be cut shorter for custom application. Conforms to ASME/ANSI A112.14.1 for Backwater Valves.

#### **PVC Backwater Valves**



## **PVC Backwater Valves** Soc x Soc - Valve Only

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
00750		- 11			
S275P	2	1	12	055	56.10
S375P	3	2	0	055	56.21
S475P	4	1	0	055	62.27
S675P	6	1	0	055	265.30

# **PVC Backwater Valves with Extension Kit to Premade Length**



# **PVC Backwater Valves with Extension Kit to Premade**

#### Soc x Soc - Assembled with Extension

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
S275P-120 <sup>1</sup>	2X12HT	1	0	055	169.21
S275P-160 <sup>1</sup>	2X16HT	1	0	055	182.01
S275P-2001	2X20HT	1	0	055	194.80
S275P-240 <sup>1</sup>	2X24HT	1	0	055	207.60
S275P-360 <sup>1</sup>	2X36HT	1	0	055	218.04
S275P-480 <sup>1</sup>	2X48HT	1	0	055	239.64
S375P-120 <sup>1</sup>	3X12HT	1	0	055	169.21
S375P-160 <sup>1</sup>	3X16HT	1	0	055	182.01
S375P-2001	3X20HT	1	0	055	194.80
S375P-240 <sup>1</sup>	3X24HT	1	0	055	207.60
S375P-360 <sup>1</sup>	3X36HT	1	0	055	218.04
S375P-480 <sup>1</sup>	3X48HT	1	0	055	239.64
S475P-120 <sup>1</sup>	4X12HT	1	0	055	219.79

# **PVC Backwater Valves with Extension Kit to Premade**

### Soc x Soc - Assembled with Extension (continued)

					- /
Part Number	Size	Std	Mstr	Disc	Price
rait Nullibei	Size	Pk	Ctn	Code	Each
S475P-160 <sup>1</sup>	4X16HT	1	0	055	237.11
S475P-2001	4X20HT	1	0	055	252.89
S475P-2401	4X24HT	1	0	055	269.66
S475P-3601	4X36HT	1	0	055	283.20
S475P-480 <sup>1</sup>	4X48HT	1	0	055	311.22
S675P-1201	6X12HT	1	0	055	461.53
S675P-1601	6X16HT	1	0	055	497.93
S675P-2001	6X20HT	1	0	055	531.07
S675P-2401	6X24HT	1	0	055	566.35
S675P-3601	6X36HT	1	0	055	594.74
S675P-480 <sup>1</sup>	6X48HT	1	0	055	653.55
1 - Size designates nor	ninal valvo cizo v ovtonci	n hair	ht (HT	ton of v	alve to top of

Size designates nominal valve size x extension height (HT-top of valve to top of extension, inches)

## **PVC Service-Access Extension Kit Only to Premade** Length



PVC Service-Access Extension Kit: includes factory assembled internal flap assembly, assembly extension pipe, and external extension housing with top access adapter. Requires solvent cement assembly to existing valve and uses existing threaded Access Plug. Standard Extensions are available in convenient increments of 12", 16", 20", 24", 36", and 48" (measured from top of valve to top of extension). Contact Spears® for pricing on custom cut lengths. All extension kits can be cut shorter in the field for custom fits prior to cementing access adapter in place.

# **PVC Service-Access Extension Kit Only to Premade**

Longin					
Part Number	Size	Std	Mstr	Disc	Price
		Pk	Ctn	Code	Each
SAEK-020-120 <sup>1</sup>	2X12HT	1	0	055	52.77
SAEK-020-160 <sup>1</sup>	2X16HT	1	0	055	54.28
SAEK-020-200 <sup>1</sup>	2X20HT	1	0	055	55.72
SAEK-020-240 <sup>1</sup>	2X24HT	1	0	055	58.39
SAEK-020-360 <sup>1</sup>	2X36HT	1	0	055	61.15
SAEK-020-480 <sup>1</sup>	2X48HT	1	0	055	64.14
SAEK-030-120 <sup>1</sup>	3X12HT	1	0	055	57.23
SAEK-030-160 <sup>1</sup>	3X16HT	1	0	055	64.60
SAEK-030-200 <sup>1</sup>	3X20HT	1	0	055	68.44
SAEK-030-240 <sup>1</sup>	3X24HT	1	0	055	77.13
SAEK-030-360 <sup>1</sup>	3X36HT	1	0	055	91.24
SAEK-030-480 <sup>1</sup>	3X48HT	1	0	055	107.91
SAEK-040-120 <sup>1</sup>	4X12HT	1	0	055	85.34
SAEK-040-160 <sup>1</sup>	4X16HT	1	0	055	96.21
SAEK-040-200 <sup>1</sup>	4X20HT	1	0	055	118.67
SAEK-040-240 <sup>1</sup>	4X24HT	1	0	055	129.95



### DWV **Industrial PVC Backwater Valves**

Backwater Valves are designed to prevent backflow in numerous applications where easy service access for maintenance and cleaning is needed. Excellent for use in sanitary or storm sewer drainage systems to prevent waste back up due to inadequate drainage, for balancing multi-level ponds, aquaculture features or storage tank systems, and many other applications. Spears Backwater Valve has been engineered for improved function and easier service, especially in buried service with use of optional Service-Access Extension available either preassembled with valve or as an add-on kit.

- · Replaceable internal flapper assembly with EPDM Seat.
- Service-Access Extension available either preassembled with valve, as an add-on kit, or as valve & extension kit components with user supplied pipe.
- Direct Connection to ASTM D 2665 PVC DWV or other IPS size pipe. Spears® fabricated IPS x Sewer Adapters or DWV x Sewer & Drain Adapter Bushings are available for connection to ASTM D 3034 & ASTM D 2729 Sewer pipe.
- Pressure Rated to 43 psi (100 feet of head) @ 73°F (23°C).
- All extension kits can be cut shorter for custom application.
- Conforms to ASME/ANSI A112.14.1 for Backwater Valves.

#### **PVC Backwater Valves**



## **PVC Backwater Valves** Soc x Soc - Valve Only

Part Number	Size	Std Pk	PIIt Qty	Disc Code	Price Each
S275P	2	1	3840	055	56.10
S375P	3	2	210	055	56.21
S475P	4	1	54	055	62.27
S675P	6	1	30	055	265.30

## **PVC Backwater Valves with Extension Kit to Premade** Length

Soc x Soc - Assembled with Extension (continued)

000 X 000 7130	Cilibica With Ext	,,,,,,,	,,,	minimu	,u)
Part Number	Size	Std	Pllt	Disc	Price
Part Number	Size	Pk	Qty	Code	Each
S375P-480 <sup>1</sup>	3X48HT	1	15	055	239.64
S475P-120 <sup>1</sup>	4X12HT	1	18	055	219.79
S475P-160 <sup>1</sup>	4X16HT	1	12	055	237.11
S475P-2001	4X20HT	1	30	055	252.89
S475P-240 <sup>1</sup>	4X24HT	1	30	055	269.66
S475P-3601	4X36HT	1	30	055	283.20
S475P-4801	4X48HT	1	30	055	311.22
S675P-1201	6X12HT	1	30	055	461.53
S675P-1601	6X16HT	1	30	055	497.93
S675P-2001	6X20HT	1	30	055	531.07
S675P-2401	6X24HT	1	30	055	566.35
S675P-3601	6X36HT	1	30	055	594.74
S675P-4801	6X48HT	1	1	055	653.55
1 - Size designates no	minal valve size x extension	on heig	ht (HT-	top of v	alve to top of

extension, inches)

## **PVC Backwater Valves with Extension Kit to Premade Length**



## **PVC Backwater Valves with Extension Kit to Premade** Length

## Soc x Soc - Assembled with Extension

Part Number	Size	Std	Pllt	Disc	Price		
	Size	Pk	Qty	Code	Each		
S275P-120 <sup>1</sup>	2X12HT	1	98	055	169.21		
S275P-1601	2X16HT	1	98	055	182.01		
S275P-2001	2X20HT	1	98	055	194.80		
S275P-240 <sup>1</sup>	2X24HT	1	98	055	207.60		
S275P-3601	2X36HT	1	98	055	218.04		
S275P-4801	2X48HT	1	98	055	239.64		
S375P-120 <sup>1</sup>	3X12HT	1	36	055	169.21		
S375P-160 <sup>1</sup>	3X16HT	1	15	055	182.01		
S375P-2001	3X20HT	1	15	055	194.80		
S375P-240 <sup>1</sup>	3X24HT	1	15	055	207.60		
S375P-360 <sup>1</sup>	3X36HT	1	15	055	218.04		

## **PVC Service-Access Extension Kit Only to Premade** Length



PVC Service-Access Extension Kit: includes factory assembled internal flap assembly, assembly extension pipe, and external extension housing with top access adapter. Requires solvent cement assembly to existing valve and uses existing threaded Access Plug. Standard Extensions are available in convenient increments of 12", 16", 20", 24", 36", and 48" (measured from top of valve to top of extension). Contact Spears® for pricing on custom cut lengths. All extension kits can be cut shorter in the field for custom fits prior to cementing access adapter in place.

## **PVC Service-Access Extension Kit Only to Premade** Lenath

Part Number Size	Std	Pllt	Disc	Price	
Fait Nullibei	Size	Pk	Qty	Code	Each
SAEK-020-120 <sup>1</sup>	2X12HT	1	65	055	52.77
SAEK-020-160 <sup>1</sup>	2X16HT	1	36	055	54.28
SAEK-020-2001	2X20HT	1	5	055	55.72
SAEK-020-240 <sup>1</sup>	2X24HT	1	5	055	58.39
SAEK-020-360 <sup>1</sup>	2X36HT	1	5	055	61.15
SAEK-020-480 <sup>1</sup>	2X48HT	1	5	055	64.14
SAEK-030-120 <sup>1</sup>	3X12HT	1	65	055	57.23
SAEK-030-160 <sup>1</sup>	3X16HT	1	36	055	64.60