



Expansion Joints Short Repair Couplings

Space Saving, Compact Version of Standard Repair Coupling
Requires 1/3 less Space

(SH119) Socket x Socket



(SH118) Spigot x Socket

- Compact Telescoping Design
- Socket x Socket Configuration for Pipe Repair or Use as a Short-Stroke Expansion Joint
- Spigot x Socket Configuration for Replacing Damaged Fittings
- Both Configurations can be Easily Modified for Opposite Use
- Available in PVC White, Sizes 1/2" - 2"
- EPDM Double O-ring Seal
- Pressure Rated to 235 PSI @ 73°F (23°C)
- NSF® Certified for Potable Water Use

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC - Spig x Soc PVC White with EPDM O-ring



SH118-05	1/2	36	0	025	5.28
SH118-07	3/4	30	0	025	6.00
SH118-10	1	35	0	025	6.93
SH118-12	1-1/4	25	0	025	13.05
SH118-15	1-1/2	32	0	025	14.21
SH118-20	2	15	0	025	21.98

PVC - Soc x Soc PVC White with EPDM O-ring



SH119-05	1/2	40	0	025	5.28
SH119-07	3/4	30	0	025	6.00
SH119-10	1	30	0	025	6.93
SH119-12	1-1/4	20	0	025	13.05
SH119-15	1-1/2	21	0	025	14.21
SH119-20	2	12	0	025	21.98

Dimensions



Size	L1	L2	L3	L4	L5	S	M
1/2	5-7/8	4-5/16	4-15/16	7/8	3/4	2	1-7/16
3/4	6-9/16	4-3/4	5-7/16	1	13/16	2-1/4	1-3/4
1	6-13/16	4-3/4	5-9/16	1-1/8	15/16	2-3/16	2-1/16
1-1/4	7-15/16	5-11/16	6-5/8	1-1/4	1	2-1/2	2-7/16
1-1/2	8-1/4	5-13/16	6-3/4	1-3/8	1-1/8	2-13/16	2-11/16
2	10-1/16	7-3/8	8-5/16	1-1/2	1-3/16	3-1/8	3-1/4

INSTALLATION NOTE: For expansion joint applications, install with unit 1/2 extended. System must be supported and blocked against thrusts and movement under pressure. May be installed with flow in either direction.