CONTROLS - SEQUENCERS & LIMIT THERMOSTATS

THERMODISC®

SEQUENCERS




Control	Timing		
Switch	(seconds)		

SUPCO® P/N	Volt	On	Off	ОЕМ	
Q101	24	1-20	40-110	Goodman® B1290906 Lennox® 12F20 & 58C9701 York® 525-37322-000	
Q102	24	30-90	1-30	Carrier® 40CF680020	
Q103	24	1-20	40-110	ICP® / Carrier® HN67QC005 ICP® / Carrier® HQ1056789	
Q104	24	30-90	1-30	Goodman® BT1256504 York® 525-37325-000 ICP® / Carrier® HN67QC006	
Q105	24	1-110	1-110	York® 525-37327-000	
Q106	24	1-110	1-110	ICP® / Carrier® HN67QC008 ICP® / Carrier® P284-1313	
Q107	24	1-160	1-160	York® 525-37328-000	
Q108	24	1-25	65-115	Goodman® B13707-38 ICP® / Carrier® HN67GJ002	
Q109	24	20-50	40-110	Janitrol® BT1256500	
Q110	24	10-30	30-60	Weatherking® 4223115608	
Q111	24	10-40 10-30	90-160 (M1-M2) 30-60 (M3-M4)	Weatherking® 4223115606	
Q112	24	10-30 10-30 10-30	90-150 (M1-M2) 30-60 (M3-M4) 30-60 (M5-M6)	Weatherking® 4223115607	
Q113	240	10-30	15-65	Klixon® 6000E4-40 Mars® 33265	
Q114	24	15-45	15-25	Coleman® 7670-307, 7670-308 7670-130, 7670-913, 7670-101	
Q115	24	1-60	1-45	Coleman® 3120A377	
Q116	24	1-60	1-45	Coleman® 3110-354	

References to other manufacturers' names, models, trademarks and part numbers are used for identification purposes only and SUPCO® replacement products are not in any way affiliated, endorsed or sponsored by such other manufacturers.

28 800.333.9125

GAS FURNACE LIMIT THERMOSTATS



- Direct OEM replacements
- Compact, versatile and cost-effective

SUPCO® P/N	Description	Open °F	Close °F	Diff. °F
SHL501	L170-40 SPST	170°	130°	40°
SHL502	L180-30 SPST	180°	150°	30°
SHL503	L190-40 SPST	190°	150°	40°
SHL504	L240-40 SPST	240°	200°	40°
SHL505	L140-40 SPST	140°	100°	40°
SHL506	L170-40 SPST	170°	130°	40°
SHL507	L140-30 SPST	140°	110°	30°
SHL508	L150-20 SPST	150°	130°	20°
SHL509	L240-30 SPST	240°	210°	30°
SHL510	L150-20 SPST	150°	130°	20°
SHL511	L160-20 SPST	160°	140°	20°
SHL512	L170-20 SPST	170°	150°	20°
SHL513	L170-40 SPST	170°	130°	40°
SHL514	L180-40 SPST	180°	140°	40°
SHL515	L200-40 SPST	200°	160°	40°
SHL516	L210-40 SPST	210°	170°	40°
SHL517	L220-50 SPST	220°	170°	50°
SHL518	L250-40 SPST	250°	210°	40°
SHL519	L155-30 SPST	155°	125°	30°
SHL520	L100-20 SPST	100°	80°	20°
SHL521	L200-20 SPST	200°	180°	20°
SHL522	L160-20 SPST	160°	140°	20°
SHL523	L130-20 SPST	130°	110°	20°
SHL524	L170-20 SPST	170°	150°	20°
SHL525	L180-20 SPST	180°	160°	20°