
FORK EXTENSIONS- FE-5-63-R

APPROX WEIGHT: 173.90 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



STANDARD FEATURES

MODEL NUMBER IS FE-5-63-R

FORK EXTENSION WIDTH: 6 1/8"±1/8"

OVERALL WIDTH W/ LOOP: 7 3/8"

USABLE WIDTH: 5 1/2"

OVERALL LENGTH: 66 1/8"

USABLE LENGTH: 55" / 63"

FITS 5" WIDE x 2" MAX. THICKNESS FORK

SOLID STEEL CONSTRUCTION

TOUGH BAKED IN POWDER COATED YELLOW FINISH

APPROX. WEIGHT / LOST LOAD = 173.90 LBS. PER PAIR MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED FORK EXTENSIONS DO NOT INCREASE THE LOAD CENTER OF EXISTING FORK TRUCK. NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES. DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING. FORK EXTENSIONS MUST NOT EXCEED 150% ORIGINAL FORK LENGTH.

SPECIAL FEATURES

NONE

REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS

[] As marked [] As drawn

Printed Name:

Signed:

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME:

VESTIL MANUFACTURING DRAWN BY: SR

DATE: 5/5/10

Χ

SALES: X SCALE: 1:10 FILE NAME:

reference: X QUOTED LEAD TIME: $_{
m Y}$

R

٧

QUOTE #

08-007-224

W.O.#

DIMENSION TOLERANCE ± 1/4"