PREMIUM TRUCK SCISSOR DOCK LIFT - WL-100-8-88
ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 96" STANDARD FEATURES **OVERALL LENGTH** MODEL NUMBER: WL-100-8-88 UNIT TO BE MOUNTED: AT SURFACE OR IN PIT (CIRCLE ONE) CAPACITY (EVENLY DISTRIBUTED): 8.000 LBS OVERALL PLATFORM SIZE: (96" X 96") RAISED HEIGHT 70" ± 2" LOWERED HEIGHT: 10" REMOVABLE HANDRAILS AND 4"NON-96" 72"X 18" REMOVABLE TOE BOARDS 45" HT W/ **OVERALL SPLIT** 21" MIDRAIL **WIDTH BRIDGE** USABLE WIDTH: 88 5/8" TRUCK BRIDGE IS 72" W X 18" L AT ROLLER END W/ CHAINS & HANDLES FRAME SIZE IS: 86 1/2" W X 92 1/2" L SHIPPING WT APPROX: 3900 LBS ± 6 1/2 HP POWER UNIT (SEE BOTTOM LEFT CORNER) W/8' OF HYDRAULIC HOSE ** STANDARD UNIT NOT INTENDED FOR SIDE CROSS LOAD -HAND-HELD CONTROL ON A 4'-20' COIL CORD REFER TO THE UNIT'S ELECTRICAL DIAGRAM FOR ELECTRICAL SERVICE REQUIREMENTS -INSTALL TO MEET ALL APPLICABLE STATE & LOCAL **CODES FOR YOUR AREA!** 5" BEVELED TOE GUARD **ELECTRIC TOE GUARDS** ARCHITECTURAL REVIEW FOR CORRECTNESS OF PIT AND FOR 70" COMPLIANCE TO LOCAL AND STATE **RAISED** CODES IS RECOMMENDED. **HEIGHT** 10" UNIT IS DURABLE LIQUID PAINT LOWERED: **BROWN FINISH** HANDRAILS ARE TOUGH BAKED IN **HEIGHT** POWDER COATED YELLOW FINISH DIMENSION TOLERANCE ± 1/4" **HOSE & CORD EXIT** -SAFETY MAINTENANCE PROPS FRAME THIS END SPECIAL FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS NONE REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE R AND LOCAL REGULATIONS AND STANDARDS UNITS REQUIRING APPROVAL DRAWINGS OR 0 MODIFIED ARE NON-RETURNABLE ٧ [] As drawn [] As marked Α HYDRAULIC UNIT OVERALL DIMENSIONS 14"W x 33"L x 31"H Signed: **Printed Name:** (COMES W/ 8FT HOSE) LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME: **POWER** AC VESTIL MANUFACTURING W.O.# Χ MOTOR VOLTAGE 115 230 | 460 SALES: X DIS DEDICATED CIRCUIT REQUIRED 60Hz 12/11/2015 reference: X SCALE: 1:36 FILE NAME: MOTOR PHASE SINCLE **THREE** QUOTED LEAD TIME: X 05-007-315 QUOTE # CONTROL **HAND**